



# EXPLORER® 110

Terminal specification

Thrane & Thrane



➤ Inmarsat's Broadband Global Area Network service – BGAN – is accessible via a small, lightweight, satellite terminal, which is quick to set up and easy to use. And you can use the same device worldwide.

A range of terminals is available, providing performance options to suit different operational needs. The service is accessed via BGAN LaunchPad, a software interface, which is standard across all terminals.



## The smallest, lightest device in the range

The Thrane & Thrane EXPLORER 110 combines an exceptionally compact design with performance and optimal flexibility. The terminal can be separated into two parts, so users can choose between indoor and outdoor use, with no need for an external antenna.

Combined with the EXPLORER ISDN handset for voice telephony and text messages, the terminal is ideal for single users, who need to set up a complete broadband mobile office in frequently changing locations.

### Applications

- **Remote access** – high-speed access to your corporate network, enabling access to company and customer information.
- **Internet** – access the internet at speeds up to 384kbps.
- **Email** – send and receive email via the internet or email applications.
- **Telephony** – make phone calls via a peripheral handset at the same time as accessing data applications.
- **Streaming** – select guaranteed quality of service up to 64kbps on demand eg. for video, audio.
- **File transfer** – send and receive large files.
- **Store and forward** – save and send files eg. video.

### Key benefits

**Ultimate portability** – at around half the size of a laptop and weighing less than 1 kg, it is the smallest and lightest terminal in the range.

**Simultaneous voice and broadband data** – access your data applications and make a phone call at the same time, via the EXPLORER ISDN handset. The terminal can also be configured and monitored directly from the handset.

**Highly flexible** – uniquely designed to split into two separate units, so the antenna can be placed outside, while you work indoors in comfort – with no requirement for an additional external antenna. The terminal can be connected to a laptop via the USB port, Bluetooth or Ethernet.

**Global coverage** – provides service anywhere within the BGAN coverage area.

**Easy to use** – with the one-patch antenna design, it takes less than a minute to locate a satellite communications signal. The service can be accessed via BGAN LaunchPad on your laptop, an EXPLORER ISDN handset or an on-box user interface with self-explanatory indicators.

**Robust** – purposely designed to operate in challenging environmental conditions.

**Completely secure** – connect seamlessly via your preferred VPN application.

## Physical characteristics

<b>Weight</b>	< 1.0kg (2.2lbs)
<b>Dimensions</b>	Length: 200mm (7.9") Width: 150mm (5.9") Depth: 40mm (1.6")
<b>Interfaces</b>	USB (with adapter) Bluetooth (up to 20m) - Supported profiles: - Service discovery application - Serial port - Dial-up networking - Headset profile - Cordless telephony Ethernet - static and dynamic IP addressing RJ-45 (for EXPLORER ISDN handset)
<b>User access</b>	Via activated 3G compatible SIM card
<b>User interfaces</b>	
<b>PC</b>	BGAN LaunchPad
<b>On terminal</b>	Audio and LED

## Power

<b>Power supply</b>	AC or DC
<b>External power</b>	12 Volts DC, 110 – 240 Volts AC
<b>Battery life</b>	
Typical use	Transmit time: 5 hours Stand-by time: 36 hours
<b>Battery type</b>	Lithium-ion. Rechargeable
<b>Input voltage</b>	10.8-15.6 Volts DC

## Tolerances

<b>Ambient operating temperature</b>	
Powered from external	DC -20°C to +55°C (+4°F to +131°F)
Powered by battery only	-20°C to +55°C (+4°F to +131°F)
<b>Charging temp</b>	0°C to +55°C (+32°F to +131°F)
<b>Operating humidity</b>	Relative humidity: 95% non-condensing at +40°C (+104°F)
<b>Water and dust (Ingress protection)</b>	IP 44

## Radio specifications

<b>Maximum radiated power (EIRP)</b>	+10dBW
--------------------------------------	--------

## Supported operating systems

<b>Operating system</b>	Windows: 98SE, 2000, XP MAC: OS 10.1 or later Linux: Redhat 9
-------------------------	---

## Data capabilities

<b>IP data</b>	
Standard IP	Background class of service Send: Up to 240kbps over a shared channel Receive: Up to 384kbps over a shared channel
Streaming IP	Guaranteed quality of service Send: 32, 64kbps Receive: 32, 64kbps
<b>ISDN data</b>	N/A
<b>SMS</b>	160 characters

## Voice capabilities

<b>Voice</b>	4kbps
<b>Supplementary services</b>	Voicemail Call forwarding Call barring Call waiting Call holding

## Accessories

<b>Cabling</b>	USB (1.8m)/Ethernet (2m)	S
<b>Voice handset</b>	Wired: EXPLORER ISDN handset (with 2m cable)/ other ISDN phones Wireless: Bluetooth handset	O
<b>AC/DC power supply</b>	110/240 Volts	S
<b>Power plug</b>	2 pin European type	S
<b>Car charger</b>	DC carplug cable, DC/DC adapter 10-31 Volts DC	O
<b>Solar charger</b>	Off the shelf (please check with manufacturer)	O
<b>Pole mount kit</b>	Fixing brackets: window mounting kit based on tripod camera mounting thread wall mount and clamp	O
<b>Spare battery</b>	Standard EXPLORER 110 battery (5 hours use, 36 hours stand-by)	O
<b>Bag</b>	Soft bag	O
<b>Other</b>	Antenna cable (3m/10m/20m) to connect the indoor and outdoor units in 'split' configuration DC/DC adaptor – input 10-31Volts DC Colour variations	O

S Standard O Optional



## How to buy

The Thrane & Thrane range of terminals is also available from more than 100 Thrane & Thrane partners worldwide, covering Europe, Africa, the Middle East, Asia, North and South America. Visit [www.thrane.com](http://www.thrane.com) to select the best supplier for you.

## About Thrane & Thrane

Thrane & Thrane is the world's leading manufacturer of terminals and land earth stations for global mobile satellite and radio communications. Since its incorporation in 1981, the company has established a strong position within global mobile satellite services based on the Inmarsat system, and today it provides equipment for land-based, maritime and aeronautical use. The company is listed on the Copenhagen Stock Exchange. [www.thrane.com](http://www.thrane.com)

## [inmarsat.com/explorer110](http://inmarsat.com/explorer110)

Whilst the above information has been prepared by Inmarsat in good faith, and all reasonable efforts have been made to ensure its accuracy, Inmarsat makes no warranty or representation as to the accuracy, completeness or fitness for purpose or use of the information. Inmarsat shall not be liable for any loss or damage of any kind, including indirect or consequential loss, arising from use of the information and all warranties and conditions, whether express or implied by statute, common law or otherwise, are hereby excluded to the extent permitted by English law. INMARSAT is a trademark of the International Mobile Satellite Organisation, Inmarsat LOGO is a trademark of Inmarsat (IP) Company Limited. Both trademarks are licensed to Inmarsat Global Limited. © Inmarsat Global Limited 2007. All rights reserved. BGAN EXPLORER 110 spec May 2007.